







ZHEJIANG HANGCHA IMP. & EXP. CO., LTD.

Factory site: 666 Xiangfu Road,
Hangzhou, Zhejiang, China (311305)

Tel: +86-571-88926735 88926755
Fax: +86-571-88926789 88132890

sales@hcforklift.com
www.hcforklift.com



Follow us on
Facebook



Follow us on
YouTube



Follow us on
WeChat



Download "Hangcha
Forklift" App



ISO14001
ISO14001:2015



ISO9001
ISO9001:2015



HANGCHA trucks conform
to the European Safety
Requirements.

HANGCHA GROUP CO., LTD. reserves the right to make any changes without notice concerning colors, equipment, or specifications detailed in this brochure, or to discontinue individual models. The colors of trucks, delivered may differ slightly from those in brochures.


2020 VERSION 1/COPYRIGHT 2020/10



XB Series Pallet Truck With Scissor Lift

The World of Hangcha
SINCE 1956





XB Series Pallet Truck With Scissor Lift Specification

			HANGCHA GROUP CO.,LTD.		
			2005XB	1510XB	1020XB
01	Manufacturer				
02	Model		2005XB	1510XB	1020XB
03	Rated load	(kg/lb)	500/1100	1000/2200	2000/4400
04	Platform lift height	(m/in)	2/78.7	1.5/59	1/39.4
05	Overall length	(m/in)	1.51/59.4	1.51/59.4	2.07/81.5
06	Overall width	(m/in)	0.68/26.8	0.68/26.8	0.8/31.5
07	Overall height	(m/in)	1.2/47.2	1.2/47.2	1.2/47.2
08	Height with rails folded	(m/in)	0.46/18.1	0.43/16.9	0.45/17.7
09	Platform size	(m/in)	1×0.68/39.4×26.8	1×0.68/39.4×26.8	1.5×0.8/59×31.5
10	Ground clearance	(m/in)	0.06/2.4	0.06/2.4	0.06/2.4
11	Turning radius inside	(m/in)	0	0	0
12	Turning radius outside	(m/in)	1.45/57	1.45/57	2.04/80.3
13	Batteries	(V,AH)	24,70	24,70	24,100
14	Weight ±30	(kg/lb)	340/750	340/750	490/1080
15	Travel speed km/h	(mph)	0~2.8(0~1.74)	0~2.8(0~1.74)	0~2.8(0~1.74)
16	Gradeability		6%	6%	6%

Wide applicability

/ Flexible device movement, quick and convenient operation, large loading capacity, high lifting height.

High structural strength

/ High strength rectangular tube, Self-lubricating nylon slider, long service life and stable performance.

High performance

/ Permanent magnet motor, One-piece hydraulic power pack, colloidal maintenance-free battery, high performance,stable and efficient.

Reliability

/ Side support system, one-way throttle valve on lifting hydraulic cylinder, Waterproof connector, safety and reliability in performance.

Safety


/ Three emergency braking functions, emergency reverse button on Joystick, electronic lift limit, ensure the safety of personnel and cargo.

Maintenance convenience

/ The battery is removed from the side of chassis, One piece plastic cover, easy to maintaining.



Double scissors structure, rectangular tube profile, more stable and stronger



One-piece cover, covering almost all important components, convenient for maintenance



The batteries can be removed conveniently, for easier maintenance and disassembly



Integrated hydraulic unit, compact structure, less space



Multi-function handle, reliable, beautiful and simple, all functions can be completed with one hand